

Ethane, Purity

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Date of Issue: 08/16/2024

Version: 1.0

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture
Product Name: Ethane, Purity
Synonyms: Ethyl Hydride

1.2. Intended Use of the Product

Industrial Uses

1.3. Name, Address, and Telephone of the Responsible Party

Company

Williams Inc.
One Williams Center
Tulsa, OK 74172
855-945-5762
www.williams.com
ehs@williams.com

1.4. Emergency Telephone Number

CHEMTREC:
1-800-424-9300 (US/Canada)
+01 703-527-3887 (International)
Security.OperationsCenter@williams.com

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture


GHS-US/CA Classification

Flammable gases Category 1 H220
Gases under pressure Liquefied gas H280
Simple Asphyxiant

2.2. Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)



Signal Word (GHS-US/CA)

: Danger

Hazard Statements (GHS-US/CA)

: H220 - Extremely flammable gas.
H280 - Contains gas under pressure; may explode if heated.
May displace oxygen and cause rapid suffocation.

Precautionary Statements (GHS-US/CA)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381 - In case of leakage, eliminate all ignition sources.
P403 - Store in a well-ventilated place.
P410+P403 - Protect from sunlight. Store in a well-ventilated place.

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions. Contact with gas escaping the container can cause frostbite.

2.4. Unknown Acute Toxicity (GHS-US/CA)

No additional information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

Ethane, Purity

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

3.2. Mixture

Name	Synonyms	Product Identifier	% *	GHS Ingredient Classification
Ethane	Ethyl hydride / ETHANE	(CAS-No.) 74-84-0	95 – 100	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Simple Asphyxiant
Propane	Normal propane / PROPANE / n-Propane / R290	(CAS-No.) 74-98-6	< 3	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Simple Asphyxiant
Methane	Marsh gas / Methyl hydride / Methane, compressed / Monomethylamine	(CAS-No.) 74-82-8	< 3	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Simple Asphyxiant

Full text of H-statements: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%). Composition is variable.

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). First aid personnel should wear appropriate protective equipment during any rescue.

Inhalation: First, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate respiratory protective equipment, use the buddy system), then remove the exposed person to fresh air. Keep at rest in a position comfortable for breathing. Give oxygen or artificial respiration if necessary. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. If frostbite or freezing from exposure to gas/liquid escaping the container occurs: For brief contact with a small amount: Rewarm with body heat. Get immediate medical advice/attention. For extensive contact or a large amount: Immediately call a poison center/doctor and follow their advice. Specific treatment is urgent, incorrect first-aid practices will aggravate the injury. Protect affected area with a loose cover until proper medical treatment is received.

Eye Contact: Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists. If frostbite or freezing occurs, immediately flush with plenty of lukewarm water to GENTLY warm the affected area. Do not use hot water. Do not rub affected area. Get immediate medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Asphyxia by lack of oxygen: risk of death. May cause frostbite on contact with the liquid.

Inhalation: In elevated concentrations may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death.

Skin Contact: Contact with gas/liquid escaping the container can cause frostbite and freeze burns.

Eye Contact: Contact with gas/liquid escaping the container can cause frostbite, freeze burns, and permanent eye damage.

Ingestion: Not considered a potential route of exposure, but contact with gas/liquid escaping the container can cause freeze burns and frostbite.

Chronic Symptoms: None expected under normal conditions of use.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Do not extinguish burning gas if flow cannot be shut off immediately. Extinguish secondary FIRES with appropriate materials.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Extremely flammable gas. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.

Explosion Hazard: May form flammable/explosive vapor-air mixture. Container may explode in heat of fire. Vapors are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks) and form explosive mixtures with air.

Reactivity: May react violently with halogens.

Ethane, Purity

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Fight fire remotely due to the risk of explosion. Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so. Remove containers from fire area if this can be done without risk. Use water spray or fog for cooling exposed containers. If possible, avoid spraying cold areas of equipment to avoid rapid freezing of water, which can result in heavy icing and possible blockage of pressure release valves. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank due to fire. After the fire has been extinguished, explosive, toxic atmospheres may linger. Before entering such an area, especially confined areas, check the atmosphere with an appropriate monitoring device.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂).

Other Information: Use water spray to disperse vapors.

5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Eliminate every possible source of ignition. Do not get in eyes, on skin, or on clothing. Do not breathe gas/vapors. Ensure adequate ventilation: gas will displace oxygen and cause rapid suffocation in confined areas.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Non-emergency personnel should evacuate the area of the spill and only enter after emergency personnel have declared the area safe to enter.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: First, eliminate ignition sources, evacuate unnecessary personnel, isolate, and ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

6.2. Environmental Precautions

Prevent entry to sewers and public waters.

6.3. Methods and Materials for Containment and Cleaning Up

For Containment: As an immediate precautionary measure, isolate spill or leak area in all directions. Stop leak, if possible without risk.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Stop the source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering. Absorb liquid components with non-combustible liquid-binding material. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: Asphyxiating gas at high concentrations. Do not pressurize, cut, or weld containers. Ruptured cylinders may rocket. Handle empty containers with care because residual vapors are flammable.

Precautions for Safe Handling: Do not breathe gas/vapors. Avoid prolonged contact with eyes, skin and clothing. Keep away from heat, sparks, and flame. Bond and ground containers during product transfer to reduce the possibility of static-initiated fire or explosion. Close valve after each use and when empty. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.

Storage Conditions: Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Keep in fireproof place. Cylinders should be stored upright with valve protection cap in place and firmly secured to prevent falling.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Halogens.

Ethane, Purity

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

7.3. Specific End Use(s)

Industrial Uses

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Ethane (74-84-0)		
USA ACGIH	ACGIH chemical category	Simple asphyxiant See Appendix F: Minimal Oxygen Content
Alberta	OEL TWA [ppm]	1000 ppm
Nunavut	OEL STEL [ppm]	1250 ppm
Nunavut	OEL TWA [ppm]	1000 ppm
Northwest Territories	OEL STEL [ppm]	1250 ppm
Northwest Territories	OEL TWA [ppm]	1000 ppm
Saskatchewan	OEL STEL [ppm]	1250 ppm
Saskatchewan	OEL TWA [ppm]	1000 ppm
Propane (74-98-6)		
USA ACGIH	ACGIH chemical category	Simple asphyxiant See Appendix F: Minimal Oxygen Content
USA OSHA	OSHA PEL (TWA) [1]	1800 mg/m ³
USA OSHA	OSHA PEL (TWA) [2]	1000 ppm
USA NIOSH	NIOSH REL (TWA)	1800 mg/m ³
USA NIOSH	NIOSH REL TWA [ppm]	1000 ppm
USA IDLH	IDLH [ppm]	2100 ppm (10% LEL)
Alberta	OEL TWA [ppm]	1000 ppm
Nunavut	OEL STEL [ppm]	1250 ppm
Nunavut	OEL TWA [ppm]	1000 ppm
Northwest Territories	OEL STEL [ppm]	1250 ppm
Northwest Territories	OEL TWA [ppm]	1000 ppm
Québec	VEMP (OEL TWA)	1800 mg/m ³
Québec	VEMP (OEL TWA) [ppm]	1000 ppm
Saskatchewan	OEL STEL [ppm]	1250 ppm
Saskatchewan	OEL TWA [ppm]	1000 ppm
Methane (74-82-8)		
USA ACGIH	ACGIH chemical category	Simple asphyxiant See Appendix F: Minimal Oxygen Content
Nunavut	OEL STEL [ppm]	1250 ppm
Nunavut	OEL TWA [ppm]	1000 ppm
Northwest Territories	OEL STEL [ppm]	1250 ppm
Northwest Territories	OEL TWA [ppm]	1000 ppm
Saskatchewan	OEL STEL [ppm]	1250 ppm
Saskatchewan	OEL TWA [ppm]	1000 ppm

8.2. Exposure Controls


Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Use explosion-proof equipment. Proper grounding procedures to avoid static electricity should be followed. Gas detectors should be used when flammable gases or vapors may be released. Oxygen detectors should be used when asphyxiating gases may be released. Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure all national/local regulations are observed.

Ethane, Purity

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection. Respiratory protection of the dependent type.



Materials for Protective Clothing: Chemically resistant materials and fabrics. Wear fire/flame resistant/retardant clothing.

Hand Protection: Wear protective gloves.

Eye and Face Protection: Chemical safety goggles. Faceshield as determined by task.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: An NIOSH-approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits.

Thermal Hazard Protection: Wear thermally resistant protective clothing. If material is cold, wear thermally resistant protective gloves.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Gas
Appearance	: Colorless
Odor	: Odorless
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: -89 °C (-128.2 °F)
Flash Point	: -135 °C (-211 °F)
Auto-ignition Temperature	: > 472 °C (881.6 °F)
Decomposition Temperature	: No data available
Flammability (solid, gas)	: Extremely Flammable Gas
Lower Flammable Limit	: 2.9 %
Upper Flammable Limit	: 13 %
Vapor Pressure	: 29000 mm Hg (560 psi)
Relative Vapor Density at 20°C	: No data available
Relative Density	: 0.45 (Water = 1)
Specific Gravity	: No data available
Solubility	: Water: Not miscible or difficult to mix
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available
Explosive Properties	: Contains gas under pressure; may explode if heated

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity:

May react violently with halogens.

10.2. Chemical Stability:

Contains gas under pressure; may explode if heated.

10.3. Possibility of Hazardous Reactions:

Hazardous polymerization will not occur.

10.4. Conditions to Avoid:

Direct sunlight, extremely high or low temperatures, open flames, sources of ignition and incompatible materials.

10.5. Incompatible Materials:

Strong acids, strong bases, strong oxidizers. Halogens.

10.6. Hazardous Decomposition Products:

Thermal decomposition may produce: Carbon oxides (CO, CO₂).

Ethane, Purity

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data:

No additional information available

Skin Corrosion/Irritation: Not classified

Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: In elevated concentrations may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death.

Symptoms/Injuries After Skin Contact: Contact with gas/liquid escaping the container can cause frostbite and freeze burns.

Symptoms/Injuries After Eye Contact: Contact with gas/liquid escaping the container can cause frostbite, freeze burns, and permanent eye damage.

Symptoms/Injuries After Ingestion: Not considered a potential route of exposure, but contact with gas/liquid escaping the container can cause freeze burns and frostbite.

Chronic Symptoms: None expected under normal conditions of use.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Ethane (74-84-0)	
LC50 Inhalation Rat	> 800000 ppm/4h
Propane (74-98-6)	
LC50 Inhalation Rat	> 800000 ppm (Exposure time: 15 min)
Methane (74-82-8)	
LD50 Dermal Rat	> 2000 mg/kg
LC50 Inhalation Rat	539600 ppm (Exposure time: 2 h)

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General: Not classified.

12.2. Persistence and Degradability

Ethane, Purity	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Ethane, Purity	
Bioaccumulative Potential	Not established.
Ethane (74-84-0)	
Partition coefficient n-octanol/water (Log Pow)	1.09 – 2.8 at 20 °C (at pH 7)
Propane (74-98-6)	
Partition coefficient n-octanol/water (Log Pow)	1.09 at 20 °C (at pH 7)
Methane (74-82-8)	

Ethane, Purity

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Partition coefficient n-octanol/water (Log Pow)	1.09
---	------

12.4. Mobility in Soil

No additional information available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

Additional Information: Handle empty containers with care because residual vapors are flammable. Empty gas cylinders should be returned to the vendor for recycling or refilling. Do not puncture or incinerate container.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

14.1. In Accordance with DOT

Proper Shipping Name : ETHANE
Hazard Class : 2.1
Identification Number :
Label Codes UN1032 :
ERG Number 2.1.15



14.2. In Accordance with IMDG

Proper Shipping Name : ETHANE
Hazard Class : 2.1
Identification Number :
Label Codes UN1032 :
EmS-No. (Fire) 2-F-D
EmS-No. (Spillage) : S-U



14.3. In Accordance with IATA

Proper Shipping Name : ETHANE
Hazard Class : 2.1
Identification Number : UN1032
Label Codes : 2.1
ERG Code (IATA) : 10L



14.4. In Accordance with TDG

Proper Shipping Name : ETHANE
Hazard Class : 2.1
Identification Number : UN1032
Label Codes : 2.1



SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Ethane, Purity	
SARA Section 311/312 Hazard Classes	Physical hazard - Flammable (gases, aerosols, liquids, or solids) Physical hazard - Gas under pressure Health hazard - Simple asphyxiant
Ethane (74-84-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Propane (74-98-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active	
Methane (74-82-8)	

Ethane, Purity

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active

15.2. US State Regulations

Ethane (74-84-0)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Propane (74-98-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

Methane (74-82-8)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

U.S. - Massachusetts - Right To Know List

15.3. Canadian Regulations

Ethane (74-84-0)

Listed on the Canadian DSL (Domestic Substances List)

Propane (74-98-6)

Listed on the Canadian DSL (Domestic Substances List)

Methane (74-82-8)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 01/27/2023

Revision

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

GHS Full Text Phrases:

H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

NA GHS SDS 2015 (Can, US)